




# E-1236VS With ACU-RITE 203 DRO

## Product Images


---



ANTI-FLOAT DESIGN ELIMINATES BACKLASH IN THE CROSS SLIDE




FULL LENGTH ENCLOSED SPLASHGUARD  
CONTAINS CHIPS AND COOLANT




STEADY REST FEATURES DOUBLE SEALED BALL BEARING GUIDES FOR SMOOTH MATERIAL MOVEMENTS



ELECTROMAGNETIC ASSISTED FOOT BRAKE FOR RAPID BRAKING



HEAT TREATED AND PRECISION GROUND GEARS IN THE HEADSTOCK REDUCE VIBRATION



## Description

Compact, powerful, perfection. Elite EVS lathes pack large features into compact footprints that make them perfect for schools, small shops, and engineering labs. Featuring certified Meehanite® castings, an electro-magnetic brake, three jaw chuck, ball bearing-mounted steady and follow rests, and CNC Style Lighting with enclosed splash guard, these lathes are truly Elite! CSA/CUS Certified.



## Additional Information

Stock Number	JT9-892303
Compound Slide Travel (In.)	3-1/2
Drive	EVS
Length of Gap (In.)	9-1/2
Max Tool Size (In.)	1/2 x 1/2
Motor (HP)	2HP, 230V,3ph
Number of Inch Threads	34.0000
Number of Longitudinal and Cross Feed Rates	50
Number of Metric Threads	33.0000
Overall Dimensions (L x W x H) (In.)	71 x 30 x 60
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0005 - 0.015
Range of Inch Threads (TPI)	2 - 56
Range of Longitudinal Feeds (IPR)	0.0016 - 0.046
Range of Metric Threads	0.5 - 12
Range of Spindle Speeds (RPM)	0 - 2,000
Size	12 x 36
Spindle Bore (In.)	1-9/16
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	1/4 - 2-1/2
Style (Type)	ELITE EVS
Swing Over Bed (In.)	12
Swing Over Cross Slide (In.)	7-5/16

Swing Through Gap (In.)	17-1/2
Tailstock Spindle Travel (In.)	4
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	1212
Width of Bed (In.)	7-1/2