




BDB-929 Belt Drive Bench lathe

Product Images























Description

The BDB-929 benchtop lathe is the essential step to improving your shop's capabilities. Engineered with precision induction hardened ground bed-ways and precision tapered roller bearings the BDB-929 delivers the smooth operation and rigidity needed to craft professional pieces.

| Stock Number | JT9-321379 |
|--|------------------------------|
| Carriage Travel (In.) | 26.5 |
| Compound Slide Travel (In.) | 1-7/8 |
| Max Tool Size (In.) | 1/2 |
| Motor (HP) | 3/4 HP, 115V, 1PH |
| Number of Inch Threads | 27.0000 |
| Number of Longitudinal and Cross Feed Rates | 60 |
| Number of Metric Threads | 12.0000 |
| Number of Spindle Speeds | 6 |
| Overall Dimensions (L x W x H) (In.) | 51x22x20 |
| Prop 65 | Cancer and Reproductive Harm |
| Range of Inch Threads (TPI) | 8 - 56 |
| Range of Longitudinal Feeds (IPR) | 0.0006-0.0368 |
| Range of Metric Threads | 0.5 - 3.5 |
| Range of Spindle Speeds (RPM) | 130-2000 |
| Spindle Bore (In.) | 3/4 |
| Spindle Mount | 1-1/2 x 8TPI |
| Spindle Taper with Sleeve | MT-3 |
| Steady Rest Capacity (In.) | 1-3/4 |
| Swing Over Bed (In.) | 8-3/4 |
| Swing Over Cross Slide (In.) | 5 |
| Tailstock Spindle Travel (In.) | 1-9/16 |
| Taper in Tailstock Spindle | MT-2 |
| Weight (Lbs.) | 287 |
| | |