



GH-1440-1 Lathe with Newall NMS300 DRO

Product Images



Description

The new JET GH-1440-1 and GH-1440-3 Geared Head Engine Lathes weigh over one ton and

come equipped with precision induction hardened ground bed-ways, spindle roller bearings, and high-quality steel hardened gears in the headstock for the ultimate working durability. The enclosed gearbox design, standard coolant system, and lead screw cover provide a smooth and quiet operation while maintaining peak performance. The GH-1440-1 and GH-1440-3 also includes an emergency stop within easy reach of the operator as well as a patented Electronic Chuck Key Docking Station that prevents startup without the chuck key when safely docked.

Additional Information

Stock Number	JT9-323386
Carriage Travel (In.)	37-1/2
Compound Slide Travel (In.)	3-1/2
Length of Gap (In.)	9-3/8
Max Tool Size (In.)	5/8 x 5/8
Motor (HP)	3HP, 230V, 1PH
Number of Inch Threads	40.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	23.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	74-4/5 x 28 x 46
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0004 - 0.0103
Range of Inch Threads (TPI)	4-112
Range of Longitudinal Feeds (IPR)	0.0012 - 0.0294
Range of Metric Threads	0.45-7.5
Range of Spindle Speeds (RPM)	40-1800
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	3-1/2
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	8-1/5
Swing Through Gap (In.)	20

Tailstock Spindle Travel (In.)	4-3/4
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	2336
Width of Bed (In.)	10-1/5