



GHB-1340A With Collet Closer



Description

JET geared head bench lathes feature an enclosed gearbox for smooth, quiet operation.

Precision roller bearings support the hardened and ground spindle resulting in tight tolerances. Headstock is constantly oiled during operation to keep down needed maintenance and repair. Each JET Lathe comes loaded with features you've come to expect, all backed by the industry leading JET Two Year Warranty.

Additional Information

Stock Number	JT9-321124
Carriage Travel (In.)	35
Compound Slide Travel (In.)	2-11/16
Drive	Geared Head
Length of Gap (In.)	8
Max Tool Size (In.)	5/8 x 5/8
Motor (HP)	2 HP, 230V, 1Ph
Number of Inch Threads	40.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	27.0000
Number of Spindle Speeds	8
Overall Dimensions (L x W x H) (In.)	79 x 28-1/2 x 30
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.0006 - .0130
Range of Inch Threads (TPI)	3-1/2 - 80
Range of Longitudinal Feeds (IPR)	.0018 - .0374
Range of Metric Threads	.45 - 10
Range of Spindle Speeds (RPM)	70 - 2,000
Size	13 x 40
Spindle Bore (In.)	1-3/8
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5 (MT-3)
Steady Rest Capacity (In.)	2-3/4
Style (Type)	Bench - Geared Head

Swing Over Bed (In.)	13
Swing Over Cross Slide (In.)	7-25/32
Swing Through Gap (In.)	18-3/4
Tailstock Spindle Travel (In.)	3-3/4
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	1154
Width of Bed (In.)	7-3/8