



BDB-1340A With Newall DP700 DRO



Description

JET Belt Drive Bench Lathes feature an enclosed gearbox with helical cut gears for noise

reduction and smooth operation. The full-length splash guard on all sizes prevents hot chips and fluid from contaminating the work area and the quick-change gearbox allows for fast and easy gear changes for metric threading. The optional bench shown in the image is compatible with JET Lathes and is available for purchase. Each JET Lathe comes loaded with features you've come to expect, all backed by the industry leading JET Two Year Warranty.

Additional Information

Stock Number	JT9-321130
Carriage Travel (In.)	35
Compound Slide Travel (In.)	2-11/16
Drive	Belt
Length of Gap (In.)	8
Max Tool Size (In.)	5/8 x 5/8
Motor (HP)	2 HP, 230V, 1Ph
Number of Inch Threads	38.0000
Number of Longitudinal and Cross Feed Rates	38
Number of Metric Threads	23.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	71 x 32 x 45
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0006-0.013
Range of Inch Threads (TPI)	3-1/2 - 80
Range of Longitudinal Feeds (IPR)	0.0018-0.0374
Range of Metric Threads	0.45-10
Range of Spindle Speeds (RPM)	60 - 1,240
Size	13 x 40
Spindle Bore (In.)	1-3/8
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5 (MT-3)
Steady Rest Capacity (In.)	2-5/8
Style (Type)	Bench

Swing Over Bed (In.)	13
Swing Over Cross Slide (In.)	7-25/32
Swing Through Gap (In.)	18-3/4
Tailstock Spindle Travel (In.)	3-3/4
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	1175
Width of Bed (In.)	7-3/8