



GH-2280ZX With ACU-RITE 203 DRO

Product Images



Description

The ZX-Series Large Spindle Bore Lathe provides power, precision, efficiency, and reliability to your metal shop. A one-piece cast iron base absorbs vibrations during operation to allow heavier cuts and ensure accuracy, while the universal gearbox eliminates the need to change

gears. This lathe also features a 10" three jaw scroll chuck with top reversing jaws, and an e-stop on the carriage for increased operator safety. Features you've come to expect in a JET Lathe that is backed by the industry-leading JET Two Year Warranty.

Additional Information

Stock Number	JT9-321879
Carriage Travel (In.)	74-5/16
Compound Slide Travel (In.)	5-1/8
Cross Slide Travel (In.)	12
Drive	Geared Head
Length of Gap (In.)	12
Max Tool Size (In.)	1 x 1
Motor (HP)	10 HP, 230/460, 3 Ph
Number of Inch Threads	61.0000
Number of Longitudinal and Cross Feed Rates	46/31
Number of Metric Threads	10.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	136 x 45 x 71
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.0006 - .0360
Range of Inch Threads (TPI)	1-5/8 - 72
Range of Longitudinal Feeds (IPR)	.0015 - .0900
Range of Metric Threads	.05 - 20
Range of Spindle Speeds (RPM)	25 - 1,800
Size	22 x 80
Spindle Bore (In.)	3-1/8
Spindle Mount	D1-8
Spindle Taper with Sleeve	MT-7 (MT-5)
Steady Rest Capacity (In.)	3/8 - 7-3/4

Style (Type)	Engine - Large Spindle Bore
Swing Over Bed (In.)	22
Swing Over Cross Slide (In.)	13
Swing Through Gap (In.)	29-1/2
Tailstock Spindle Travel (In.)	5
Taper in Tailstock Spindle	MT-5
Weight (Lbs.)	6933
Width of Bed (In.)	13-1/8