



# GH-1440B with Acu-Rite 203 DRO

## Product Images

---





## Description

---

This new JET GH-1440B Geared Head Bench Lathe is engineered for smooth, quiet operation and user versatility. Positioned on a heavy-duty cast iron stand with a newly added built-in footbrake, the GH-1440B includes precision induction hardened ground bed-ways, spindle roller bearings, and high-quality steel hardened gears in the headstock for ultimate working durability. The GH1440B also includes a patented electronic chuck key docking station that prevents startup without the chuck key when safely docked.

## Additional Information

|                                             |                                |
|---------------------------------------------|--------------------------------|
| Stock Number                                | JT9-323440                     |
| Carriage Travel (In.)                       | 37-2/5                         |
| Compound Slide Travel (In.)                 | 3-1/2                          |
| Cross Slide Travel (In.)                    | 7                              |
| Length of Gap (In.)                         | 8                              |
| Max Tool Size (In.)                         | 4/5 x 4/5                      |
| Motor (HP)                                  | 2 HP, 230V, Single Phase       |
| Number of Inch Threads                      | 34.0000                        |
| Number of Longitudinal and Cross Feed Rates | 32/32                          |
| Number of Metric Threads                    | 26.0000                        |
| Number of Spindle Speeds                    | 8                              |
| Overall Dimensions (L x W x H) (In.)        | 76-13/32 x 29-29/32 x 59-13/16 |
| Prop 65                                     | Cancer and Reproductive Harm   |
| Range of Cross Feeds (IPR)                  | 0.007 -0.0187                  |
| Range of Inch Threads (TPI)                 | 4-56                           |
| Range of Longitudinal Feeds (IPR)           | 0.002 -0.0548                  |
| Range of Metric Threads                     | 0.4-7                          |
| Range of Spindle Speeds (RPM)               | 70-1900                        |
| Spindle Bore (In.)                          | 2                              |
| Spindle Mount                               | D1-5                           |
| Spindle Taper with Sleeve                   | MT6                            |
| Steady Rest Capacity (In.)                  | 0.31-2.95                      |
| Swing Over Bed (In.)                        | 14                             |
| Swing Over Cross Slide (In.)                | 8                              |

|                                |      |
|--------------------------------|------|
| Swing Through Gap (In.)        | 20   |
| Tailstock Spindle Travel (In.) | 4    |
| Taper in Tailstock Spindle     | MT4  |
| Weight (Lbs.)                  | 1753 |
| Width of Bed (In.)             | 7.32 |